



### 10/7 CFT – Hydraulic Concrete Machine with hopper fed

#### SPECIFICATION


TYPE	TILTING TYPE
Drum Capacity	Unmixed 10 CFT, Mixed 7 CFT
Drum Speed	22 RPM
Concrete Mixing Time	180 Seconds Approximate
Prime Move	5HP Air Cooled Diesel Engine 5HP 3 Phase Electric Motor
Transportation	Tractor New Tyres & Resole Maruti Tyre
Over All Dimensions	L-2450 x W-1250 x H-1850mm
Mixing Drum	1. Heavy Duty Drum & MS Blades For Efficient Mixing 2. Cone Made Out of 10 gauge sheet
Chassis	MS Steel (SAIL/MC/VIZAG 100×50)



## 10/7 CFT Concrete Mixer Machine (Hopper Type)

### SPECIFICATION

TYPE	TILTING TYPE
Drum Capacity	Unmixed 10 CFT, Mixed 7 CFT
Drum Speed	22 RPM
Concrete Mixing Time	180 Seconds Approximate
Prime Move	5HP Air Cooled Diesel Engine 5HP 3 Phase Electric Motor
Transportation	Tractor New Tyres & Resole Maruti Tyre
Over All Dimensions	L-2450 x W-1250 x H-1850mm
Mixing Drum	<ol style="list-style-type: none"> <li>1. Heavy Duty Drum &amp; MS Blades For Efficient Mixing</li> <li>2. Cone Made Out of 10 gauge sheet</li> </ol>
Chassis	MS Steel (SAIL/MC/VIZAG 100×50)



## 10/7 CFT Mixer cum Lift

### SPECIFICATION

TYPE	TILTING TYPE
Drum Capacity	Unmixed 10 CFT, Mixed 7 CFT
Drum Speed	22 RPM
Concrete Mixing Time	180 Seconds Approximate
Prime Move	102 mm/10HP Air Cooled Diesel Engine 10HP 3 Phase Electric Motor
Transportation	New Tyre 6:00:16 Tractor Model
Over All Dimensions	L-2745 x W-1830 x H-3050mm
Mixing Drum	<ol style="list-style-type: none"> <li>1. Heavy Duty Drum &amp; MS Blades For Efficient Mixing</li> <li>2. Cone Made Out of 10 gauge sheet</li> </ol>
Chassis	MS Steel (SAIL/MC/VIZAG) 125×65
Tower Channel	MS Steel (SAIL/MC/VIZAG) 100×50
Bucket Capacity	10/7 CFT
Wire Rope	10mm (Usha Martin)



## 10/7 CFT Builder's Hoist

### SPECIFICATION


MODEL	SURYA BH 200
Capacity	10/7 cuft. (280/200 ltrs)
Lifting Height	25 mtrs. to 45 mtrs.
Carrying Skip	10 cuft. With 12 mm dia wire rope
Speed	25-30 Mtrs / Min
Power Unit	12 HP/ 14 HP / 18 HP HSD Double Cylinder Air / water cooled Diesel Engine OR 12.5 HP / 15 HP / 440/3/50 Electric Motor OR A high capacity Primemover



## 10/7 CFT Concrete Mixer Machine

### SPECIFICATION

TYPE	TILTING TYPE
Drum Capacity	Unmixed 10 CFT, Mixed 7 CFT
Drum Speed	22 RPM
Concrete Mixing Time	180 Seconds Approximate
Prime Move	5HP Air Cooled Diesel Engine 5HP 3 Phase Electric Motor
Transportation	Tractor New Tyres & Resole Maruti Tyre
Over All Dimensions	L-2450 x W-1250 x H-1850mm
Mixing Drum	<ol style="list-style-type: none"> <li>1. Heavy Duty Drum &amp; MS Blades For Efficient Mixing</li> <li>2. Cone Made Out of 10 gauge sheet</li> </ol>
Chassis	MS Steel (SAIL/MC/VIZAG 100×50)



### 5/3.5 CFT Hand Fed Mixer Machine

#### SPECIFICATION

TYPE	TILTING TYPE
Drum Capacity	Unmixed 10 CFT, Mixed 7 CFT
Drum Speed	22 RPM
Concrete Mixing Time	180 Seconds Approximate
Prime Move	5HP Air Cooled Diesel Engine 5HP 3 Phase Electric Motor
Transportation	Tractor New Tyres & Resole Maruti Tyre
Over All Dimensions	L-2450 x W-1250 x H-1850mm
Mixing Drum	<ol style="list-style-type: none"> <li>1. Heavy Duty Drum &amp; MS Blades For Efficient Mixing</li> <li>2. Cone Made Out of 10 gauge sheet</li> </ol>
Chassis	MS Steel (SAIL/MC/VIZAG 100×50)



Earth Rammer	
SPECIFICATION	
MODEL NO	SURYA 002T/SURYA 004T/SURYA 008T
Compaction Capacity	1-2 Ton/3-4 Ton/6-8 Ton
Impact Force Upto (approx.)	850 kg/1000 kg/3500 kg
Power Unit	<ul style="list-style-type: none"><li>• 1.95 HP/ 3.4 HP Petrol / Diesel OR 3HP-440/3/50 AC Electric Motor</li><li>• 4.4 Hp Diesel OR 3 HP - 440/3/50 AC Electric Motor</li><li>• 5HP Diesel OR 7.5 HP/440/3/50 Electric Motor</li></ul>



## Bar Bending Machine

### SPECIFICATION

Material	Stainless Steel
Automation	Automatic
Power	Hydraulic
Weight	2600 Kg





## Bar Cutting Machine

### SPECIFICATION

Material	Stainless Steel
Automation	Automatic
Power	Hydraulic
Weight	2600 Kg



## Reversible Mixer Machine

### SPECIFICATION

MODEL	SM 800
Hopper Capacity	800 Liters
Batch Capacity	600 Liters
Machine Output/Hour	10 to 12 Cu.Mt/Hr
Water Tank Capacity	170 Liters
Weighing System	Load Cell Based Weighing System with Digital Display
Wheel	Pnematic Wheel (4 Nos) 6" * 16"
Jack Leveling	Pne type (4 Nos.)
Size (L*W*H)	(4250*1940*2860)mm
Weight	2250 kg
Gear Ring & Roller	Accurately Machined With Gear Cutting Operation Supported By Heavy Duty Twin Rollers Guide



## Needle Vibrator

### SPECIFICATION

Prime Move

Greaves / VIJAYA 1.5 / 1.95 Petrol Start, Kerosine Run Rope Start Engine

Accessories

Cage with Conical Springs or Revolving base, Frame Stand & Needle fitting attachments

Suitable Needles


1.5 / 7.95 HO 25/30/40 mm 0 needle with 6 or 4 Meters with long flexible shaft



## Plate Vibrator

### SPECIFICATION

Frequency	2940rpm
Power	0.7KW
Weight	2.9KG
Drive Mode	Electric Vibrator



## Cube Testing Machine

### SPECIFICATION

Capacity	1000 Kg
Power	Hydraulic
Voltage	220 V
Weight	Approx 500 Kg
Piston stroke	80 mm



## Ladder Lifting Machine

### SPECIFICATION


AMC/AFTER SALES SERVICE	PROVIDED
Installation Provided	Yes
Number of Stops	0-5
Required Part(s)	Over Speed Governor
Usage	Industrial Premises



## Wheel Barrow

### SPECIFICATION

Water Capacity	90 L
Wheel	Rubber wheel
Load	150 kg
Material	Metal Tray



Grout Pump	
SPECIFICATION	
MODEL	SURYA 140
Pressure	140PSI





## 14/10 CFT Hot Mix Machine

### SPECIFICATION

MODEL	SURYA 10
Capacity	14/10 cuft.
Power Unit	10/14/16 HP Diesel Air / Water Cooled Engine